



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LL 06/30/06'		

NOTES:

- ELECTRICAL CHARACTERISTICS:
  - CONTACT RESISTANCE: 20mΩ Max.
  - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
  - INSULATION RESISTANCE: 1000MΩ Min.
- ENVIRONMENT CHARACTERISTICS:
  - TEMPERATURE: -40°C~+105°C.
- PRODUCT NUMBER CODE:

DS1002-10 - X X X X

Contact type  
 1: TYPE 1  
 2: TYPE 2  
 3: TYPE 3  
 Clip plating  
 1: Tin 150u"  
 2: Tin 200u"  
 3: G/F  
 4: Gold 3u"  
 5: Gold 10u"  
 6: Gold 15u"  
 Pin plating  
 1: Tin 150u"  
 2: Tin 200u"  
 3: G/F  
 4: Gold 3u"  
 5: Gold 10u"  
 6: Gold 15u"  
 No. of contacts  
 06 08 14 16 18  
 20 24 28 32 40  
 Series No.  
 DS1002-10

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

PROJECTION		TITLE	SIP IC SOCKET PITCH 1.778mm
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1002-10 SERIES

2	CONTACT		COPPER ALLOY		GOLD PLATED	DRAWING TYPE	CUSTOMER		
1	HOUSING		THERMOPLASTIC		UL 94 V-0	SCALE	1:1	SHEET	1 OF 1
ITEM	PART NAME	PART NO.	MATERILAS		FINISHED	DRAWING NO.	C-DS1002-10-XXXX		

**晨翔电子有限公司**  
**CONNFLY CONNFLY ELECTRONIC CO. LTD**